

NSC FT-160

Logical means of delivering Reliable UPS Power

KEY FEATURES

- Quicker & Easier Installation of NSB battery units
 - Significant reduction in installation times
- Trouble-free & Safer Maintenance and Testing of NSB battery units
 - Reduced routine maintenance times
- Quicker & Easier “swapping” of individual NSB battery units
- Breaker (optional) - 300 Amps to 600 Amps
- Shelf Guides to assist Quicker & Easier Installation
- Clean & Simple inter-cell connectors and cable management
- UL/CUL
- Seismic Z4 rated.



**159 kW Front Terminal
UPS Power Cabinet**

MECHANICAL CHARACTERISTICS

Configuration	480 or 360 Volts	
Max Capacity	159 kW (at 480 Volts)	
	<i>SI Units</i>	<i>English Units</i>
Height	1984 mm	78.1 in
Width	1511 mm	59.5 in
Depth	641 mm	25.25 in
Weight (ex. batteries)	363 kg	800 lb
Breaker (optional)	300 Amps to 600 Amps	

ADDITIONAL FEATURES

- Max. Capacity based on NSB 12-600FTs at 480 Volts
- Removable Locking Doors with quick ground disconnect
- Ample venting to promote natural convection and maximize cooling to extend battery life
- Easy accessible and moveable by forklift or pallet-jack
- Beige Powder Coat optional
- Internal cabling standard

*The information that is provided on NorthStar Battery data sheets is intended for reference only.
Please contact your sales representative for your specific application needs.*